



CATALOG CORRECTION

Catalog #115 page 9


Explanation:

The tire and wheel information chart at the bottom of page 9, has incorrect information regarding stock wheel fitment. See chart below for application. See chart in figure 1 for corrections to the chart found on page 9 of catalog #115.

APPLICATION				
MODEL	2WD / 4WD	YEAR	LIFT HEIGHT	LIFT TYPE
Pickup Avalanche Tahoe/Yukon Suburban / Yukon XL	2WD & 4WD	2007-08	6"	Knuckle with Spacer or New Strut Body

FIGURE 1

Installation Information



Tire and Wheel Information

Lift Height	Install Time	Difficulty Rating	Cutting or Welding	Max. Tire Diameter	Fender Trimming	Max. Tire Width	Min. Wheel Diameter	Wheel Width	Minimum Backspacing	Maximum Backspacing	Stock Wheels
6" Knuckle	8-9 hrs.	5	Both	33"	No	12.5"	17"	8.5"	5.5"	6"	*20" Only
6" Knuckle	8-9 hrs.	5	Both	35"	Yes	12.5"	17"	8.5"	5.5"	6"	*20" Only

***NOTE:** Cannot run a stock 17" or 18" rim, Therefore it will not run the factory spare. The use of the factory 20" rim is acceptable.